



# Product Data Sheet

## OB 40 STROKER

MARINE OUTBOARD 2 STROKE (Ashless)

### Product Description

**OB40 Stroker** is a versatile ashless high performance Two Stroke engine oil developed for marine outboards. Designed to mix easily and completely with all types of petrol in both pre-mix and oil injection systems and once mixed will not separate. Provides outstanding detergency in outboard water-cooled two-cycle gasoline engines. Provides excellent rust protection during extended engine storage periods. Does not contribute to preignition or spark plug fouling.

### Applications

Suitable for use in all fuel/oil mix Two Stroke engines, particularly outboards requiring TC-W3 grade oil. Exceeds the current requirements of Mercury, Tohatsu, Evinrude/Johnson, Suzuki, Yamaha and Mariner.

### Specifications

This product formulation meets the latest TC-W3® reformulated performance specifications.

Product Registration Number: NMMA TC-W3 RL-00417J 2009

### Packaging

205 litre drum, 20 litre pail, 5 litre pack

### Typical Physical Characteristics

Property	Typical Value
Density, kg/L	0.878
Colour	Blue
Kinematic Viscosity at 40°C, cSt	37.6
Kinematic Viscosity at 100°C, cSt	6.7
Viscosity Index	136

**NOTE:** Values stated herein are typical and do not represent a specification.

**OB40 Marine 2 Stroke**